


Article	H/h, inch	Weight lb	H/h, mm	Weight kg
04707133409/410	16,1	366,4	410	166,5
04707133409/405	15,9	364,8	405	165,8
04707133409/400	15,7	363,3	400	165,1
04707133409/395	15,6	362,4	395	164,7
04707133409/390	15,4	360,2	390	163,7
04707133409/385	15,1	358,7	385	163,0
04707133409/380	15,0	357,1	380	162,3
04707133409/375	14,8	355,6	375	161,6
04707133409/370	14,5	354,1	370	160,9
04707133409/365	14,4	352,5	365	160,2
04707133409/360	14,2	350,9	360	159,5
04707133409/355	13,8	349,4	355	158,8
04707133409/350	13,8	347,8	350	158,1
04707133409/345	13,6	346,3	345	157,4
04707133409/340	13,2	344,7	340	156,7
04707133409/335	13,2	343,1	335	156,0
04707133409/330	13,0	341,6	330	155,3
04707133409/325	12,5	340,0	325	154,5
04707133409/320	12,6	338,4	320	153,8
04707133409/315	12,4	336,9	315	153,1
04707133409/310	12,4	335,3	310	152,4
04707133409/305	12,0	333,7	305	151,7
04707133409/300	11,8	332,2	300	151,0
04707133409/295	11,7	330,6	295	150,3
04707133409/290	11,4	329,1	290	149,6
04707133409/285	11,2	327,5	285	148,9
04707133409/280	11,1	326,3	280	148,3
04707133409/275	10,8	324,8	275	147,6
04707133409/270	10,6	323,3	270	146,9
04707133409/265	10,5	321,7	265	146,2
04707133409/260	10,2	320,2	260	145,5

Article	H/h, inch	Weight lb	H/h, mm	Weight kg
04707133409/410-405	16,1/15,9	365,6	410/405	166,2
04707133409/405-400	15,9/15,7	364,0	405/400	165,5
04707133409/400-395	15,7/15,6	362,5	400/395	164,8
04707133409/395-390	15,6/15,4	360,9	395/390	164,1
04707133409/390-385	15,4/15,2	359,4	390/385	163,4
04707133409/385-380	15,2/15	357,9	385/380	162,7
04707133409/380-375	15/14,8	356,3	380/375	162,0
04707133409/375-370	14,8/14,6	354,8	375/370	161,3
04707133409/370-365	14,6/14,4	353,2	370/365	160,6
04707133409/365-360	14,4/14,2	351,7	365/360	159,9
04707133409/360-355	14,2/14	350,2	360/355	159,2
04707133409/355-350	14/13,8	348,6	355/350	158,5
04707133409/350-345	13,8/13,6	347,1	350/345	157,8
04707133409/345-340	13,6/13,4	345,5	345/340	157,1
04707133409/340-335	13,4/13,2	344,0	340/335	156,4
04707133409/335-330	13,2/13	342,5	335/330	155,7
04707133409/330-325	13/12,8	340,9	330/325	155,0
04707133409/325-320	12,8/12,6	339,4	325/320	154,3
04707133409/320-315	12,6/12,4	337,8	320/315	153,6
04707133409/315-310	12,4/12,2	336,3	315/310	152,9
04707133409/310-305	12,2/12	334,8	310/305	152,2
04707133409/305-300	12/11,8	333,2	305/300	151,5
04707133409/300-295	11,8/11,6	331,7	300/295	150,8
04707133409/295-290	11,6/11,4	330,1	295/290	150,1
04707133409/290-285	11,4/11,2	328,6	290/285	149,4
04707133409/285-280	11,2/11	327,1	285/280	148,7
04707133409/280-275	11/10,8	325,5	280/275	148,0
04707133409/275-270	10,8/10,6	324,0	275/270	147,3
04707133409/270-265	10,6/10,4	322,4	270/265	146,6
04707133409/265-260	10,4/10,2	320,9	265/260	145,9

Article	H/h, inch	Weight lb	H/h, mm	Weight kg
04707133409/410-400	16,1/15,7	364,8	410/400	165,8
04707133409/400-390	15,7/15,4	361,7	400/390	164,4
04707133409/390-380	15,4/15	358,6	390/380	163,0
04707133409/380-370	15/14,6	355,5	380/370	161,6
04707133409/370-360	14,6/14,2	352,4	370/360	160,2
04707133409/360-350	14,2/13,8	349,4	360/350	158,8
04707133409/350-340	13,8/13,4	346,3	350/340	157,4
04707133409/340-330	13,4/13	343,2	340/330	156,0
04707133409/330-320	13/12,6	340,1	330/320	154,6
04707133409/320-310	12,6/12,2	337,0	320/310	153,2
04707133409/310-300	12,2/11,8	334,0	310/300	151,8
04707133409/300-290	11,8/11,4	330,9	300/290	150,4
04707133409/290-280	11,4/11	327,8	290/280	149,0
04707133409/280-270	11/10,6	324,7	280/270	147,6
04707133409/270-260	10,6/10,2	321,6	270/260	146,2

1. Dimensions for reference, inch [mm]
2. Delivery and packaging are carried out in accordance with the terms of the contract
3. The manufacturer reserves the right, without notice to the consumer, to make changes to the design of the products for improvement of their technological and operational parameters, which will not affect the quality and properties of the product
4. Deviation of the actual weight of the nominal can be up to 10%.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: ISO 2768 - C LINEAR: ANGULAR:		FINISH:	DEBURR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING	REVISION
DRAWN Kyselytsia		SIGNATURE	DATE 08.09.23	 TITLE: 12"[DN300] Concrete Drain Channel Pro H10.2"-16.1"[H260-410] vertical outlet 7.8"[200] with Cast Iron Grate D400	
CHK'D Kyselytsia					
APPV'D Malynovskiy					
MFG					
QA		MATERIAL: Concrete, Cast Iron	ARTICLE:	A3	
WEIGHT: lb / kg			SCALE:1:9	SHEET 1 OF 1	